1

5 Method, computer-based-system and virtual asset register

TECHNICAL FIELD.

The present invention is concerned with a method and computer-
based system for controlling, monitoring and/or maintaining

10 equipment in an electrical power distribution system. In
particular it is concerned with a database consistency method
and computer-based system that enables consistent retrieval,
synchronisation and storage of data between a plurality of
databases containing information and data relative to operating

15 an electrical power network.

TECHNICAL BACKGROUND
Electrical power distribution network systems for industrial and
residential power users typically comprise many and various
types of distribution equipment located over a large geographic

20 area. Most utilities operating a geographically distributed
asset such as an electrical power network need a suit of IT
support systems to manage the operation and maintenance of the
assets. Today there is no common way of information integration

25 between these systems which makes information retrieval
difficult when more than one system is involved. For example, a
power transformer device must be known in several systems. The
customer information system has knowledge what customers are
connected to the transformer. The Network Information system

30 (NIS or GIS) has information about the geographical location of
the transformer. The ERP system (Enterprise Resource Planning)
has the maintenance history of the transformer and the SCADA
system (Supervisory Control and Data Acquisition) knows the
actual performance measurements, temperature, voltages and so on

35 of the transformer.

A successful integration of a GIS (Geographical Information
System) system, preferably with other systems such as a real
time SCADA system with an ERP system would make power network
information available to the ERP system. US 6,564,201 B1,
5   entitled Expert designer system virtual plug-in interface;
describes virtual plug-in interface for an expert designer
system for use with one or more database system types operates.
These systems include a geographic information system (GIS) and
a work management system (WMS). It is described that the virtual
10   GIS plug-in interface interacts with the GIS such that the
expert designer system core functions independently of the type
of GIS database system. The document discloses use of object-
oriented programming architectures to make a virtual interface
for GIS and/or WMS systems which is independent of specific
15   database type or manufacturer and simplifies the task of
designing GIS databases.

Integration of ERP and GIS database systems would facilitate
automatic creation of work orders from the ERP system for
20   condition-based maintenance dependent on more automatic or
manually controlled outputs from, for example, a SCADA system.
For example maintenance could be scheduled on a basis of
accumulated short circuit limits for a given breaker. Another
example would be automatic generation of work orders for
25   inspecting a protection device used with low frequency a
distribution or a feeder line. It would also be possible to
validate that future scheduled maintenance activities is
permissible with respect to other maintenance activities,
switching status, available power production resources,
30   transmission capabilities and forecasted consumption and so on.

One complication to be dealt with is that changes in the power
grid assets would need to be reflected in the IT systems. In
addition, several types of power devices need to be modelled in
35   more than one IT system. For example, a power transformer device
must be known in several systems an example previously

2

mentioned. For example, the customer information system (CIS) has knowledge of which customers are connected to the transformer, the NIS system has information about the geographical location of the transformer, the ERP system has the

5   maintenance history of the transformer and the SCADA system has the real time and stored measurements taken at the transformer.

Within the power industry and network management industry a common approach to document exchange and conversion, CIM, Common

10 Information Model, has been developed around the use of XML-based formats. More information on current practices and method for use of CIM/XML (Common Information Model/eXtensible Markup Language) for data exchange within the electrical power industry may be obtained from North American Electricity Reliability

15 Council (NERC), Federal Energy Regulatory Commission (FERC). The CIM/XML standards greatly facilitate the exchange and automatic conversion of documents produced by one supplier of a part of the network or an equipment for the network so that a second supplier can receive, handle and re-use the technical data from

20 the original documents without manual intervention, editing or re-inputting.

However there is a series of difficult challenges to be overcome to achieve the kind of integration desired for the separate IT

25 systems described. A demand facing utility network owners and operators is to extract more value from the existing assets in a network utility, in terms of higher output without causing increased maintenance work, breakdowns or equipment loss. Another demand is to be able to integrate IT systems so as to

30 make information accessible to all users who have an interest in the network. Manual linking and connections have been made in the past to exchange data between different IT systems, and to reconcile data for consistency. However this has been done manually or on a batch basis and has not been practically

35 implemented on a real-time basis. The task of integrating separate IT systems is complicated. In particular, there is a

difficult technical problem of sharing data between different
databases and at the same time achieving and maintaining data
consistency between multiple IT systems. In addition, the real-
time nature of power network operation demands of that data

5   retrieval and/or communication can work at high speeds in a
network utility and in an automated and effective way.

SUMMARY OF THE INVENTION
The present invention aims to solve one or more of the above

10   problems.

According to one aspect of the invention, the object is achieved
by the initially defined method.

15   According to another aspect of the invention, the aims are
achieved by a software architecture including a consistency and
mapping layer based on a structured text standard.

According to another aspect of the invention, the aims are

20   achieved by register of power network held by a computer-based
system.

According to another aspect of the invention, the aims are
achieved by a computer-based system.

25

A major advantage of the present invention is that integration
is carried out in such a way that data across the different
systems is kept consistent. In addition, the invention provides
as well a new and better platform with which to support asset

30   management applications.

The system integration achieved by the invention provides
interface and access advantages for users of power network
systems such as:

35   a series of User Interface navigation displays used and operated
by users with standard object-oriented navigation, selection,

input and display methods. The displays give timely access to
all relevant information, and from all integrated IT systems.
The integrated systems comprise data and data representations
that are context sensitive, and provide simple and unified ways
5   to navigate between different functional views, technical views
or contextual views of the same process equipment, device,
installation or other network asset. In addition the invention
provides advantageously for one consistent asset representation
using the Virtual Asset Register (VAR), with single data entry,
10 automatic synchronization, data exchange between applications
and both mapping to CIM/XML model as well as import & export to
CIM/XML. The integrated systems do not require any other special
provisions and may, for example, use applications that can work
on one or more generic CIM models. The all-important consistency
15 checks may take place in the background, and be thus not visible
or apparent to a user.

The integrated systems provided by the invention have the
advantage of providing means for:
20 -reduced data maintenance cost for the network,
-optimised service life of equipment,
-increased quality of asset data, and
-improved decision support.

25 As much of the invention is implemented in software and may be
implemented by means of novel software architectures the
necessary time and capital cost of including the invention in
both new installations and existing installations is relatively
low and therefore also very advantageous for that reason.
30
According to another aspect of the invention, the aims are
achieved by (one or more) a computer program directly loadable
into the internal memory of a computer or processor, comprising
software code portions for performing the steps of the method(s)
35 according to the invention, when said program is run on a
computer or processor. The computer program is provided either

on a computer readable medium or through a network, a high-speed
private network, such as a local area network or a wide area
network including the Internet.

5   According to still another aspect of the invention, the objects
are achieved by a computer-readable medium having at least one
program recorded thereon, where the program is to make a
computer or processor perform the steps of the method according
to the invention, when said program is run on a computer or
10   processor.

BRIEF DESCRIPTION OF THE DRAWINGS
Embodiments of the invention will now be described, by way of
example only, with particular reference to the accompanying
15   drawings in the attached presentation file which:

Figure 1 shows a schematic block diagram of different IT systems
and databases integrated by a CIM/XML layer and an HMI layer
according to an embodiment of the invention.
20

Figure 2 shows a schematic block diagram of integrated and
different IT systems and databases in which the CIM/XML layer
comprises a Virtual Asset Register and a data exchange
middleware and supports an asset optimization application
25   according to another embodiment of the invention.

Figure 3 is a table or matrix over functions, purposes and
implementations for data exchange and other applications in a
power network according to an embodiment of the invention.
30

Figure 4 shows a schematic block diagram of both predictable and
condition based maintenance in provided by data exchange and
other applications such as a CMMS (Computerised maintenance
management system) in a power network.
35

Figures 5, 6, 7 show stages in a method for handling alarms and faults using an HMI to interface both a SCADA system and a maintenance or CMMS application in connection with data exchange and other applications in a power network according to another
5   embodiment of the invention.

Figures 8, 9 show stages of a method for handling alarms and faults using an HMI to interface objects in both a SCADA system and a maintenance or CMMS application to GIS system data for the
10 same object(s) in connection with data exchange and other applications in a power network according to another embodiment of the invention.

Figures 10, 11 show representations of steps in alarm handling
15 using an HMI to interface objects in SCADA, maintenance or CMMS, GIS wherein information about an object, a breaker, from a maintenance or technical information database is simultaneously accessed, according to another embodiment of the invention.

20 Figure 12 is a schematic block diagram of different local IT systems and databases integrated by a CIM/XML layer using XLST transforms to map global objects to local objects consistently according to an embodiment of the invention.

25 Figure 13 is a schematic block diagram of different IT systems and databases integrated by a CIM/XML layer using adapters to map the XML, attribute changes and object according to an embodiment of the invention.

30 Figures 14, 15, 16 show schematic overviews for data consistency between different local IT systems and databases SCAD, ERP and GIS integrated by a CIM/XML layer, and with respect to mapping and attribute conflicts.

35 Figure 17 shows a schematic overview including data from a GIS system in respect of a new object added to the network;

Figure 18 shows schematically how that same new object may also
be recognized in the SCADA and ERP systems, according to an
embodiment of the invention; and

5   Figure 19 shows a flowchart for a method according to an
embodiment of the invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

10 Figure 1 shows schematically three separate systems which are
each operating in a part of a power network. It shows a SCADA
(Supervisory Control and Data Acquisition) system 2a, with a
database 2b; a GIS (Geographical Information System) system 3a
with a database 2b, and a CMMS (computerised maintenance
15 management system) 4a and database 4b. A wall 7 is shown
symbolically separating each system. A first layer 1 is shown
bridging the otherwise separate IT systems. Layer 1 is a CIM/XML
layer for data consistency and/or synchronisation. A user
interface navigation layer 5 which, as will be described in more
20 detail later, also comprises one or more HMIs and is also shown
bridging the otherwise separate systems.

Figure 2 shows schematically an architecture in more detail. It
shows separate IT systems for operations of the power network
25 such as SCADA, EMS (Energy Management System)2a and DMS
(Distribution Management System) 2b; a maintenance system such
as a CMMS 4a, b; and GIS or NIS systems 3,a, b. The IT systems
are connected via a middleware EAI (Engineering Application
Integration) layer 14 and a Virtual Asset Register (VAR) 10 to a
30 user interface navigation layer 5' that comprises one or more
HMIs. Also included in the architecture are one or more
applications for asset management 12.

Figure 3 shows in a matrix form various network operation
35 functionalities, under the heading Customer value, with a
comment or expanded explanation under the heading Comment, and

possible implementations under the heading Mapping. It shows in Step 1 that the Navigation functions of the present invention are context sensitive, depending on which context i.e. which system is currently activated by the user, which is achieved and

5　implemented by object and object-oriented architecture to enable linking between the representations of the same object in all systems. Step 2 shows that Consistency means that objects may be added and or deleted in a consistent way across all systems, implemented by a grouping function, a hierarchical parent-child

10　type of grouping model using object-oriented references also referred to as structures; and that data exchange is carried out consistently and based on a CIM model and implemented by means of checking attributes of the objects in the separate IT systems for consistency with stored values for such attributes.

15

Step 3, Asset Optimization is primarily concerned with optimising the service life of equipment in the network, for example by means of an optimised balance between condition-based maintenance and/or predictable maintenance and/or planned

20　maintenance. This may be carried out by the use of a CIM/XML model and mapping between systems, eg mapping from a given fault object reported by a SCADA system to the same given object held in a maintenance system such as a CMMS system, which mapping is carried out by means of the virtual asset register (VAR) as

25　described in more detail below with reference to Figures 12, 13.

Figure 4 shows an optimised example for handling maintenance faults according to an embodiment of the invention. The figure shows an equipment 40 monitored by a SCADA system, and modeled

30　on an HMI of a operation system 41. The figure shows that an operator 43 may provide operator input through an application 43c of the HMI which may be communicated to a Predictable Maintenance (PM) or Work Order (WO) application 45b of a PM or WO system. The figure also shows that the SCADA system collects

35　data from field devices 43a, such as the above equipment 40, and provides alarms and/or data events, parameters etc 48 to a

PM system 44. Automation equipment can trigger work orders based on real time information from the equipment itself, for example operational hours, fieldbus information, maintenance triggers or software agent-type maintenance triggers. It can further be seen

5   that as well as data collection from devices, direct input 43b from a control centre operator and/or direct input 45c from an engineer in the field with a portable device may be received by the PM system and be then available to the other systems. The Work Order (WO) system may be a part of or module for a

10   maintenance system, or it may be a part of an ERP (Enterprise Resource Planning) system. Alternatively direct input 43b may be generated by an automatic, computerised process instead of or as well as a human operator.

15   Figure 5 shows in more detailed description a stage of handling a fault in an equipment similar to that fault described in relation to Figure 4. A fault is reported by the SCADA system, in Bay 5, 50 and the faulty object may be selected on a screen of an HMI of a Navigation System accessing the SCADA system

20   data. The user is then presented with options, in this example by means of a drop-down window 51. Figure 6 shows how the user may select Active Work Orders 52 to check the current maintenance situation for this object, a breaker. An interface element, in this case the window 51, accessing Active Work Order

25   status 53 retrieved from a maintenance system such as a CMMS (Computer managed maintenance system), shows the faulty equipment, the object, and any active work orders for it. Figure 7 shows how, using a fault reporting element 55 of the HMI interface, the user may file a fault report which may become the

30   basis of a new work order. This also corresponds to the fault report 43c of Figure 4.

Figure 8 presents information about the same selected faulty object 40', the breaker, from the Geographical Information

35   System (GIS), giving an overview of the geographical location of the breaker. Figure 9 presents a view of the HMI with which a

user may access a work order, in this case the new work order 63
for the breaker by means of options in a drop down window
operable from the selected screen object from the location
display provided by GIS information.

5

Figure 10 is similar to Figure 5, showing the faulty equipment
with options displayed, with in this case, an option to access
59 the Maintenance and Service Manual for the selected object,
the breaker, which produces product documentation 100. Figure 11

10 shows how the HMI in the Navigation Interface System integrates
information and access for the same selected object so that the
SCADA system information 50, the GIS system information 40', the
CMMS work order information 63 and the CMMS Technical Manual
information 100 may presented for a user to see, access and/or

15 manipulate at the same time. In addition, distance and/or route
to a site may be seen simultaneously from the GIS information
which facilitates determining which repair crew should be
dispatched and what extra factors concerned with distance to
site, time to site and/ or details of site topology need to be

20 considered. The display shown by Figure 11 comprises then
information from separate IT systems, SCADA, GIS, CMMS, that is
to say, data and/or information accessed in the separate IT
systems and retrieved at the same time and displayed together by
the computer-based system for the user. The user has full access

25 to data held by each of the IT systems by provided by the
invention, which data is maintained in a fully consistent state
by the consistency mechanisms of the invention.

Figure 19 shows the above method in the form of a flowchart.

30 Some of the steps of the method are carried out by means of
computer programs. The steps of the method in this exemplary
example begin with a signal from one particular IT system of the
network, in this case and not exclusively, beginning at 80 with
a SCADA report, in this case and not exclusively in the practice

35 of the invention, a fault report. At 81 the faulty object is
selected on a display by a user, operator. This step may

alternatively be carried out by a process running in a computer, that, in effect, executes a process that has the equivalent effect of selecting the faulty object. At 82 a user checks maintenance information, for example to see what work orders are

5   active in a CMMS system. The SCADA system is operated 84 to isolate an equipment and to restore the network to an operating condition; this may be done by an operator, a process in a computer, or by a combination. This means then that the SCADA system is operated, ie control signals are generated by the

10   SCADA system so as to switch lines and/or equipment on or off, in this case, for the purpose of isolating an equipment or part of a line. At 85 a fault report may be created by the operator in the CMMS system 86, or semi-automatically, or automatically by CMMS. On the basis of the information provided in the

15   computer-based system from SCADA, CMMS and GIS, an operator or a pre-programmed process may dispatch a work crew 87 to a fault location, such that the crew as well as other users of the computer-based system has access to the GIS geographical information, map, to find the best route to the location. At the

20   same time, product documentation is retrieved 89 and accessed 90 so that detailed maintenance information for the equipment of interest is simultaneously available throughout the computer-based system for any validly logged on user.

25   Figure 12 shows in a schematic block diagram an overview of the global-local relationships, and that part of how data consistency is maintained. Figure 12 shows local databases, accessible in relation to local objects, linked to a set of global objects comprised in a virtual asset register (VAR).

30   The figure shows a local SCADA database 2b, a GIS database 3b and a CMMS database 4b. It also shows a VAR 10 linked by adapters or in this case transform means XLST 2t, 3t, 4t to a local object, 2o, 3o, 4o, and thus by means of those two functional elements to each of the three local databases 2b, 3b,

35   4b. Global objects which are based on a CIM/XML model are maintained in the VAR 10 as links to objects, not objects as

such, only in the form of cross-reference and mapping data for
each object in the power network.

The XLST transforms are a preferred adapter implementation for
5   translating the XML based CIM model data into a format that can
operated on local objects 2o, 3o, 4o which provide access and
retrieval, read and write access, into the local SCADA, GIS and
CMMS databases. This access is not necessarily identical and may
well be different for different systems or databases. All
10   participating applications must provide read and write access to
their data sets through APIs (database access, OPC access,
direct API access), where APIs are Application Programming
Interfaces and OPC is an industry standard for linking or
locating data called Object (Linking and Embedding) for Process
15   Control.

The VAR 10 consists of the following components:
-A global CIM/XML based data model for exchange of data between
the involved applications (typically GIS, CMMS and SCADA)
20   -A mechanism and means for Data Consistency. If an object is
created or modified in one of the systems, the changes are
reflected also in the other systems. This means that the object
is automatically created or the attributes are changed in the
other systems. The data consistency checking may be run as a
25   real-time process or alternatively may be run as a batch job
that is run once a day for example.
-a database, preferably an SQL (Structured Query Language)
database, for example an Oracle (TM) or MS SQL Server (Microsoft
SQL server TM) that contains cross-reference/mapping tables for
30   objects in the different applications and tables of object types
that describe what attributes the objects have in each
application. This is especially important when each application
has its own names for the same objects and attributes. It should
be noted that this database contains only cross-reference and
35   mapping data: in this sense it is a virtual asset register (VAR)
because it does not contain the actual object data as such. It

contains only the cross-reference and mapping data and the
actual data that describes each object is stored in each
applications database, that is, in the SCADA system, the GIS
system, the CMMS system and so on.

5

Figure 13 shows the arrangement of Figure 1 with the role of
adapters, such as the adapters shown and described in relation
to Figure 12. The figure shows a possible inclusion of
applications known as Message oriented Middleware (MoM). It also
10   shows that other database systems Na may optionally be included
in the computer-based system as well as SCADA, GIS, CMMS
systems. For example other related and/or legacy systems such as
CIS, PM, WMS, WOS.

15   Figure 14 shows a display and input member for consistency
checking between the separate IT systems. It shows a SCADA
system 2, SAP (CMMS) system 4, and an ESRI (GIS/NIS) system 3.
(SAP is a trademark). Figure 15 shows a schema for mapping
between global objects and local objects which is part of the
20   consistency checking functions described in relation to Figure
14. It can be seen in this example that CIM-type Global
substation objects LoadArea, MemberOF, name and Description are
in this case mapped to the following local substation objects
GENERALPROPERTIES.LOADAREA, GENERALPROPERTIES.MEMEBEROF,
25   NAME.NAME and NAME.DESCRIPTION respectively. Figure 16 shows
conflict handling within the consistency functionality. Here it
may be seen that one three IT systems, AIP 117, ESRI 118 and SAP
119 are available fro a user or engineer to select as Master
data or source data to resolve a potential consistency conflict.

30

Figure 17 shows the insertion of a new object 170 in a display
from a GIS system. Figure 18 shows a combination of the GIS and
a synchronization window 180, which may be a part of the data
consistency functions. It may be seen that the GIS system ESRI
35   has flagged a new object substation.xsd, and options are
presented to Insert in SCADA 189, or insert in SAP 187. The

option to insert in ESRI 188is grayed, as the object has already
been detected as inserted in the GIS system ESRI.

The integration may be implemented by means of a SCADA system
5   with a SCADA user interface, of the WS500 type of the Spider
system for SCADA provided by ABB, and a CMMS maintenance
management system from IFS, a NIS or GIS system such as ESRI
planning & mapping system and a HMI integration platform and/or
application integration platform such as an ABB Industrial IT
10   system from ABB. The invention demonstrates a seamless user
interface integration between SCADA, CMMS or GIS with context
sensitive access to CMMS from SCADA or GIS (by means of object
linking) in a computer-based system comprising access to those
separate IT systems described.
15
The invention makes it possible to operate one or more parts of
one or more power networks as one global or enterprise level
data model of the assets (CIM+).

20   Attribute consistency - updating attribute values (overlapping)
Object consistency - adding/deleting objects:
Single data entry
One consistent enterprise level: Virtual Asset Register (VAR)
Add new object (in all relevant systems)
25   Object created in each system based on object templates
Connections between systems established automatically
Delete object (in all relevant systems)
Delete defined object in each system
Delete object connections (links)
30   Access object attributes (all)
Select object by identifier (any system)
Read out any object property independent of source
Modify object attribute(s)
Select object by identifier (any system)
35   Update attribute in source system (owner)
Replicate data to other systems (readers of the data)

Maintain object connections (links)

Power network equipment in an Energy Management System (EMS) or
Distribution Management System (DMS) may include any combination
5   or combinations of transmission lines, distribution lines,
transformers or reactors of various types, switchyards,
substations, protection devices, live tank circuit breaker,
disconnector, switch-disconnector or load disconnector, earthing
switch, disconnector circuit breaker, dead tank circuit breaker,
10   gas-insulated circuit breaker, gas-insulated disconnector,
earthing switch, switchgear modules including CBs, DCs, SDs etc
as above.

CIM, Common Information Model, is an industry standard approach
15   in the Energy Management System industry covering the use of XML
formats in data exchange. More information on current practices
and method for use of CIM/XML for data exchange within the
electrical power industry may be obtained from North American
Electricity Reliability Council (NERC), Federal Energy
20   Regulatory Commission (FERC).

The CIM language includes a set of class diagrams that use the
UML, Unified Modeling Language. CIM/XML may be described as the
incorporation of elements from the RDF (Resource Description
25   Framework, as defined by W3C) data model to form CIM/XML. For
example by using an RDF element, a URI (Uniform Resource
Identifier), to represent resources. Resources may correspond
to objects and properties may correspond to object attributes.

30   An XML grammar, as defined in a suitable DTD (Document Type
Definition) can be used both to represent CIM declarations
(classes, instances and qualifiers) and CIM messages for use by
the CIM mapping onto another protocol such as HTTP. Mapping with
an XML derivative may be carried out using any suitable
35   approach, such as schema mapping in which the XML Schema is used
to describe the CIM classes, and CIM Instances are mapped to

valid XML Documents for that schema; or meta-schema mapping in
which the XML schema describes the CIM meta-schema, and both CIM
classes and instances are valid XML documents for that schema.

5   Use of an XML or XML/CIM format may include the use of
stylesheets and in particular XSLT stylesheets. A well-formed
XML document may include both elements that are defined by XSLT
and elements that are not defined by XSLT. XSLT stands for
eXtensible Stylesheet Language Transform – thus it is a
10 programming language, or other means, for transforming XML
documents and rendering them in HTML or between different
formats. XSLT-defined elements are distinguished by belonging to
a specific XML namespace. A transformation expressed in XSLT is
called a stylesheet. This is because, in the case when XSLT is
15 transforming into the XSL formatting vocabulary, the
transformation functions as a stylesheet.

Other current standards capable of use for data exchange include
derived protocols such as COM (Component Object Model) Document
20 Object Model (DOM), Microsoft's (Trade Mark) MSXML and a
standard called XHTML 1.0 provided by World Wide Web Committee
(W3C). The invention is not limited to XML based implementations
and may alternatively use any derivative of a format such as the
Standard Generalised Markup Language (SGML) meta-language, or
25 Hyper Text Markup Language (HTML), eXtended Markup Language
(XML) or derivatives such as XHTML 1.0, Extended Stylesheet
Language (XSL) and the Document Object Model (DOM); or adaptions
suited for user to handle using applications on portable or
mobile devices, for example Wireless Markup Language (WML),
30 which may be used with a WAP telephone may be described as a
derivative of XML, or a WDML derivative, or WBXML.

The client applications of the HMI may be implemented as a thin
client using a structured text document or file to present any
35 of CIM/XML information, arguments, variables, addresses, links,

mappable objects, executable applications or applets, or for
example an HTML or other WWW based or HTML derivative protocol
or XML protocol. The structured text document or file format
takes care of handling graphical user display and activation
5   functions of the HMI client. Activation functions refers to
functions in the web page or web client display carried out by
executable applications or applets which may be implemented as
Java (TM) or similar. By means of such a thin client version of
the HMI with an architecture such as that shown in Figure 1, 2,
10   4, 19, a user or a technician may examine status or data,
configure a parameter, change set points and/or issue commands
remotely in to any object for which he/she has authority to so
do via the navigation interface.

15   The methods of the invention may be carried out by means of one
or more computer programs comprising computer program code or
software portions running on a one or more servers, a computer,
or a processor. The computer or microprocessor (or processors)
comprises a central processing unit CPU performing the steps of
20   the method according to one or more facets of the invention,
such as the methods described. The methods are performed with
the aid of one or more said computer programs, which are stored
at least in part in memory accessible by the one or more
processors.
25

For example a program or part-program that carries out some or
all of the steps of methods such as that described in relation
to Figure 19, may be run by a computer or processor of the
computer-based system. At least one of the servers or computers
30   may be in a central object oriented control system in a local or
distributed computerised control system. It is to be understood
that said computer programs may also be run, at least in part,
on one or more general purpose industrial microprocessors or
computers instead of one or more specially adapted computers or
35   processors.

The computer program comprises computer program code elements or
software code portions that make the computer perform the method
using equations, algorithms, data, stored values and
calculations previously described. A part of the program may be
5   stored in a processor as above, but also in a ROM, RAM, PROM,
EPROM, or EEPROM chip or similar memory means. The program in
part or in whole may also be stored on, or in, other suitable
computer readable medium such as a magnetic disk, CD-ROM or DVD
disk, hard disk, magneto-optical memory storage means, in
10   volatile memory, in flash memory, as firmware, stored on a data
server or on one or more arrays of data servers, or in high
security data storage systems. Other known and suitable media,
including removable memory media such as removable flash
memories, hard drives etc. may also be used at least in respect
15   of part of the data.

Data may also be communicated wirelessly between various parts
of a power network, and/or to or from one or more of the
different IT systems and databases. For example data may be
20   collected from sensors arranged on equipment on a line or in a
switchyard or a substation, stored and communicated as necessary
by a SCADA system. Wireless communications may be carried out
using any suitable protocol, including a wireless telephone
system such as GSM or GPRS. Signals from a SCADA, CMMS or other
25   system may also be sent via wireless communication to an
equipment in a power network arranged with wireless
communication so as for example as a result of an update of
maintenance status, to activate a control, to set a breaker to
maintenance mode, or perform a control action. Short range radio
30   communication is a preferred technology, using a protocol
compatible with, standards issued by the Bluetooth Special
Interest Group (SIG), any variation of IEEE-802.11, WiFi, Ultra
Wide Band (UWB), wireless personal area network (WPAN) such as
ZigBee according to IEEE-802.15.4, IEEE-802.13 or equivalent or
35   similar. In particular a radio technology working in, for
example, the ISM band with significant interference suppression

means by spread spectrum technology is advantageous, especially communication for field devices or sensors. For example a broad spectrum wireless protocol in which each or any data packet may be re-sent at other frequencies of a broad spectrum 7 times per

5   millisecond, for example, may be used, such as in a protocol from ABB called Wireless interface for sensors and actuators (Wisa).

The computer programs described above may also be arranged in

10   part as a distributed application capable of running on several different computers or computer systems at more or less the same time. Programs as well as data such as energy related information may each be made available for retrieval, delivery or, in the case of programs, execution over the Internet.

15   Data and/or methods may be accessed by software entities or other means of the control system by means of any of the lost of: OPC, OPC servers, an object request broker such as COM, DCOM or CORBA, a web service.

20   It is also noted that while the above describes exemplifying embodiments of the invention, there are several variations and modifications which may be made to the disclosed solution without departing from the scope of the present invention as defined in the appended claims.

25